

## GUARDIAN SPECIFICATION SHEET – GS-350

### MAINTENANCE SYSTEM FOR GUARDIAN GRAFFITI SHIELD

(WATERBASED POROUS SURFACE SACRIFICIAL COATING)

#### MAINTENANCE SYSTEM –SACRIFICIAL WATERBASED

To maintain Guardian Graffiti Shield in the best performance it is recommended to remove graffiti and other marks from the coating as soon as possible

After initial application of Guardian Graffiti Shield it is recommended to allow the coating the fully dry for a 24hrs before cleaning of the surface.

Primary graffiti removal method is with hot water/steam approx. 80°C - 90°C in a spray jet procedure directly onto the surface. The temperature must be maintained at 80°C - 90°C at the surface for the coating to dissolve. Graffiti can also be removed from surfaces treated with Graffiti Shield using Guardian Graffiti Remover or Guardian Graffiti Gel and washing with high pressure water.

Guardian Graffiti Shield dissolves with hot water and graffiti remover and must be reapplied after graffiti cleaning.

For general cleaning off of dirt and grime it is recommended to clean the coating surface low pressure cold water at least every 12 months.

#### GUARDIAN SPECIFICATION GUIDE

| DEPOSITS                                                              | METHOD OF CLEANING                                                                                               | FREQUENCY OF CLEANING                                                                                                                                       |
|-----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>REMOVAL OF GRAFFITI</li> </ul> | USE HOT WATER/STEAM SPRAY JET APPROX. 80°C - 90° or GUARDIAN GRAFFITI REMOVER /GEL THEN WASH WITH WATER PRESSURE | RECOMMENDED TO CLEAN OFF GRAFFITI AS SOON AS IT APPEARS.<br><br>GUARDIAN GRAFFITI SHIELD MUST BE REAPPLIED AFTER REMOVAL OF GRAFFITI TO CONTINUE PROTECTION |
| <ul style="list-style-type: none"> <li>DIRT AND GRIME</li> </ul>      | LOW PRESSURE WASH WITH COLD WATER                                                                                | EVERY 12 MONTHS MINIMUM                                                                                                                                     |