

Guardian Walkway

Water Based Acrylic Floor Coating

FEATURES

Guardian Walkway WB is a water based acrylic floor coating, ideal for application to cement surfaces.

Guardian Walkway WB is a high build coating that is ideal for flooring application to walkways, that is specifically designed for foot traffic.

Guardian Walkway WB has a strong and durable non-skid finish. It has excellent flexibility and can be used to bridge fine cracks.

Guardian Walkway WB is a strong durable coating with excellent weathering properties.

RECOMMENDED USES

Due to its unique properties, **Guardian Walkway WB** is ideal for bridging fine cracks both interior and exterior, and is suitable for application to cement based floor surfaces.

Guardian Walkway WB can be used on walkways in domestic, commercial and trade situations. It is not designed for vehicle traffic and should not be used on driveways.

Guardian Walkway WB may also be used for exterior wall applications where a fine aggregate textured finish is required as a continuation of the floor coating.

SPECIFICATION DATA

Generic Type:	Waterborne Acrylic.	Volume Solids:	~45%.
Finish:	Low sheen	Dry Film Thickness:	* 200 µ total.
Colour:	Light & Mid Greys	Wet Film Thickness:	*225 µ per coat.
Density:	~1.36 g/cc	Coverage:	*4 m ² /L per coat
Packaging:	10 litre.	Number of coats:	2 coats
Application:	Roller and airless spray	Touch Dry:	2 - 4 hours
Thinner:	Water	Dry to Recoat:	12 hours
Cleanup:	Water.	Hard Dry:	8 - 10 hours.
		Storage:	Store under cool dry conditions.

** Note: Due to the texture effect creating a unique "profile", Coverage, WFT and DFT should be taken as a guide only.*

DIRECTIONS FOR USE

Ensure all surfaces are clean, dry, and free from oil, grease and dust. The surface should be firm and solid, with loose material removed and large cracks or holes filled. Very smooth or porous surfaces should be primed with **Guardian WB Sealer Primer**.

Guardian Walkway WB is best applied un-thinned, using a medium nap quality roller which will produce uniform thickness and appearance. A fine textured roller can be used to produce a subtle textured effect. When applying by roller, ensure the is "laid off" in one direction (downwards) to produce a uniform pattern. Roll closely to the brushed cut-in areas.

Stir well and ensure colour (if tinted) is as required before use. Provide adequate natural ventilation during use. Wash equipment immediately after use with water.

DO NOT apply if temperature is below 10°C, above 37°C, or relative humidity is above 85%.

Typical Specifications

Surface	Preparation	System	Dry Film Build
Porous and previously painted surfaces	Surfaces should be sanded with all loose flaking paint removed. Ensure that surfaces are clean, dry and dust free.	1. Guardian Primer 2. Guardian Walkway 3. Guardian Walkway	50µ 100µ 100µ
Masonry, cement render, brick	Ensure that surfaces are clean, dry and dust free.	1. Guardian Walkway 2. Guardian Walkway	100µ 100µ

PRECAUTIONS

Refer to the Safety Data Sheet (SDS) for health and safety information prior to use.

GUARDIAN PROTECTIVE COATINGS

26 Paramount Drive, Wangara, Western Australia 6065
PO Box 1473, Wangara, Western Australia 6947
Telephone (+61) 8 6389 2100 Fax (+61) 8 9302 2578
info@guardit.net
www.guardit.net.au

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.