

Guardian Anti Graffiti Primer

High Performance Acrylic Primer Water Based

Uses

- Concrete/cement
- Brick
- Brick stone, stone
- Masonry in general
- Surfaces painted with acrylic paints

Advantages

- Environmentally friendly
- Easy application
- Excellent adhesion
- Quick drying (touch dry 20 min)
- Available in Clear and White
- Water Based Acrylic

Coverage

Spread rate is between 10 m² and 14 m² (one coat) - varies depending on the type of surface and the porosity. Apply to achieve around 20 microns DFT.

Application

- Refer to the preparation and application guide in the AG top coat specification sheets
- Apply with brush, roller (low/medium nap) or airless spray
- On very porous surfaces, thin down with 10% water
- Recoat with AG top coat after 12 – 24 hours
- DO NOT apply if temperature is below 10°C, or relative humidity is above 85%.

Preparation

- Ensure surface to be coated is clean, dry (test with moisture meter if unsure) and free from contamination, including fungal or algal growth.
- Ensure surfaces repair are carried out and repair is dry
- Apply a test area, if required to ensure surface is ready for application of sealer/primer

Guardian Protective Coatings

26 Paramount Drive, Wangara, Western Australia 6065

Telephone (+61) 8 6389 2100

info@guardit.net

www.guardit.net.au