

Safety Data Sheet



Section 1 PRODUCT IDENTIFICATION	
Product Name:	Guardian Graffiti Shadow Remover
Synonyms:	none
Recommended Use:	Removal of shadow left by graffiti
Supplier Information:	Guardian Protective Coatings Pty Ltd 26 Paramount Drive Wangara WA 6055 Tel: 08 6389 2100 www.guardit.net Emergency contact: +61 413 610 147 (24 hours)
Section 2 HAZARD IDENTIFICATION	
Hazard Classification:	DANGEROUS GOODS according to the criteria of the ADG code HAZARDOUS CHEMICAL according to the criteria of Safe Work Australia Flammable Liquids, Category 2 Skin corrosion / Irritation, Category 2 Serious eye damage/eye irritation, Category 1 Specific Target Organ Toxicity (single exposure), Category 3 Specific Target Organ Toxicity (repeat exposure), Category 1 Germ Cell Mutagenicity, Category 1B Carcinogenicity, Category 1A Acute Toxicity-Dermal, Category 4 Acute Toxicity-Oral, Category 4 Acute Toxicity-Inhalation, Category 4 Aspiration hazard, Category 1 Chronic aquatic toxicity, Category 3 Label elements: Pictograms  FLAMMABLE  IRRITANT  HEALTH HAZARD  CORROSIVE Signal Word: DANGER
Hazard Statements:	H225 Highly flammable liquid and vapour H315 Causes skin irritation H318 Causes serious eye damage H335 May cause respiratory irritation H372 Causes damage to organs through prolonged or repeated exposure H340 May cause genetic defects

Safety Data Sheet



	H350 May cause cancer H312 Harmful in contact with skin H302 Harmful if swallowed H332 Harmful if inhaled H304 May be fatal if swallowed and enters airways H412 Harmful to aquatic life with long lasting consequences
Precautionary Statements:	GENERAL P101 If medical advice is needed, have product container or label at hand P102 Keep out of reach of children P103 Read carefully and follow all instructions PREVENTATIVE P210 Keep away from heat/sparks/open flames/hot surfaces – No Smoking P233 Keep container tightly closed P240 Ground/bond container and receiving equipment P241 Use explosion proof electrical/ventilation/lighting equipment P242 Use only non-sparking tools P243 Take action to prevent static discharges P261 Avoid breathing mists/vapours/spray P264 Wash thoroughly after handling P271 Use only outdoors or in a well-ventilated area P273 Avoid release to the environment P280 Wear protective gloves/eye protection/face protection RESPONSE P301+P310 IF SWALLOWED; Immediately call a Poison Centre or doctor P302+P352 IF ON SKIN: Wash with plenty of soap and water P303+P361+ IF ON SKIN (or hair): Take off immediately all contaminated clothing. P353 Rinse skin with water/shower. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+ IF IN EYES: Rinse cautiously with water for several minutes. Remove P338 contact lenses if present and easy to do. Continue rinsing. P312 Call a POISON CENTER or doctor/physician if you feel unwell P332+P313 If skin irritation occurs: Get medical advice/attention P331 Do NOT induce vomiting P337+P313 If eye irritation persists: Get medical advice/attention P362 Take off contaminated clothing and wash before reuse P370+P378 In case of fire: Use foam/water spray/fog for extinction STORAGE P403+P233 Store in a well-ventilated place. Keep container tightly closed P403+P235 Store in a well-ventilated place. Keep cool P405 Store locked up DISPOSAL P501 Dispose of contents/container in accordance with local regulations

Safety Data Sheet



Section 3 COMPOSITION

Ingredient	CAS Number	Proportion
Xylene	1330-20-7	10-30%
Diethylene glycol monobutyl ether	112-34-5	10-30%
n-Butanol	71-36-3	10-30%
Ethanol	64-17-5	10-30%
Solvent naphtha (petroleum), light aromatic	64742-95-6	10-30%
Benzyl Alcohol	100-51-6	<10%
Sodium Hydroxide	1310-73-2	<2%

Note – product contains <0.1% benzene

Proportion is % weight per weight

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS)

Section 4 FIRST AID MEASURES

Poisons Information Centres in each State capital city can provide additional assistance for scheduled poisons.

Description of necessary first aid measures

Inhalation: Keep victim calm and remove to fresh air if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

Skin Contact: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available. Transport to nearest medical facility for additional treatment if necessary.

Eye Contact: If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.

Ingestion: If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Symptoms caused by exposure

Inhalation: Breathing of high vapour concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continuous inhalation may result in unconsciousness and death.

Skin: May include burning sensation and/or a dried/cracked appearance.

Eye: May include burning sensation, redness, swelling and/or blurred vision.

Ingestion: May include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever.

Safety Data Sheet



Section 5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Foam, water spray or fog, carbon dioxide, dry chemical powder. Do not use water in a jet.

Specific Hazards:

Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible.

Fire Fighting Advice:

Class 3 Flammable liquid. On burning this product may emit toxic fumes. Heating can cause expansion or decomposition leading to violent rupture of containers. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus if risk of exposure to vapour or decomposition products.

Section 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

Environmental precautions

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterways using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.

Methods and materials for containment and cleaning up

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

Section 7 HANDLING AND STORAGE

Precautions for safe handling

Highly Flammable product. Avoid breathing vapours. Handle and open containers with care in a well ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.

Conditions for safe storage, including any incompatibilities

Bulk storage tanks should be banded. Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.

Safety Data Sheet



Section 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

National Exposure Limits.

From National Occupational Health and Safety Commission (NOHSC) Worksafe Australia

Material	TWA		STEL		Notices
	ppm	Mg/m ³	ppm	mg/m ³	
Xylene	80	350	150	655	SK
n-Butanol	50	152			
Ethanol	1000	1880			
Aromatic solvents 169-185		100			
Sodium hydroxide		2			

TWA:

The Time Weighted Average airborne concentrations over an eight-hour working day, for a five day working week over an entire working life.

STEL:

(Short Term Exposure Limit) The average airborne concentration over a fifteen minute period which should not be exceeded at any time during a normal eight-hour work day.

SK Notice:

Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

According to current knowledge, these concentrations should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These exposure standards are guides to be used in the control of Occupational Health Hazards. All atmospheric contamination should be kept as low as is practicable.

Exposure standards should **NOT** be used as the defining line between safe and dangerous concentrations of chemicals. They are **NOT** a measure of relative toxicity.

Biological monitoring

No biological limit allocated.

Engineering controls

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use. DO NOT enter confined spaces where vapour may have collected.

Individual protection measures

Eye and face protection: Wear safety goggles.

Skin protection: Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.

Respiratory protection: If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.

Thermal hazards: Not applicable

Safety Data Sheet



Section 9 PHYSICAL PROPERTIES

Appearance: Clear mobile liquid

Solubility: Insoluble in water

Odour:	Solvent	Density @ 20°C:	~0.9 kg/l
pH:	NAP	Flash point & Method:	22°C Closed Cup
Vapour Pressure 20°C (mm Hg):	NAV	Upper Explosive Limit (UEL):	NAV
Vapour Density (Air = 1)	NAV	Lower Explosive Limit (LEL):	NAV
Initial Boiling Point & Range °C:	NAV	Ignition Temperature °C:	NAV
Freezing Point °C:	NAV	Percent Volatiles (by weight):	~98%

NAP = Not Applicable, NAV = Not Available

Section 10 STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions of use.

Chemical stability

Stable under normal conditions of use.

Possibility of hazardous reactions

Stable under normal conditions of use.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials

Strong oxidising agents.

Hazardous decomposition products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

Section 11 TOXICOLOGICAL INFORMATION

Acute toxicity:	Expected to be of low toxicity - LD50 Oral (rat) > 2000 mg/kg LC50 Inhalation (rat, 4h) > 20 mg/l LD50 Dermal (rabbit) > 2000 mg/kg
Skin corrosion/irritation:	May cause moderate skin irritation. Prolonged contact may cause defatting of skin which can lead to dermatitis.
Serious eye damage/irritation:	Causes serious damage to eyes.
Respiratory or skin sensitisation:	Not expected to be a sensitiser.

Safety Data Sheet



Germ cell mutagenicity:	May be mutagenic
Carcinogenicity:	May be carcinogenic.
Reproductive toxicity:	Not expected to impair fertility
Specific Target Organ Toxicity (STOT) – single exposure:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Specific Target Organ Toxicity (STOT) – repeated exposure:	Central nervous system: repeated exposure affects the nervous system. Liver, kidneys: can cause damage
Aspiration hazard:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity

For constituent **Xylene**:

Acute Toxicity – fish: Toxic, $1 < LC/EC/IC\ 50 \leq 10\text{mg/l}$.

Acute Toxicity – invertebrates: Toxic, $1 < LC/EC/IC\ 50 \leq 10\text{mg/l}$.

Acute Toxicity – algae: Toxic, $1 < LC/EC/IC\ 50 \leq 10\text{mg/l}$.

Acute Toxicity – microorganisms Data not available

Chronic toxicity Data not available

Persistence and degradability

Data not available.

Bioaccumulative potential

Data not available.

Mobility in soil

Data not available

Other adverse effects

Data not available.

Section 13 DISPOSAL CONSIDERATIONS

Do not pour unwanted product down the drain. Keep unwanted product in sealed containers for disposal via special chemical waste collections. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty containers via domestic recycling programs may differ between local authorities. Check with your local council first.

Safety Data Sheet



Section 14 TRANSPORT INFORMATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG7 Code) for transport by road or rail.

UN Number:	1993	HAZCHEM:	•3YE
UN Proper Shipping Name:	FLAMMABLE LIQUID, NOS	Packaging Group:	II
Class and Sub Risk:	3 Flammable Liquid		

Special Precautions: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1) in bulk, poisonous gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) and radioactive substances (Class 7), however, exemptions may apply.

Section 15 REGULATORY INFORMATION

Hazardous according to Safe Work Australia

Poisons Schedule (Australia): S5

Section 16 OTHER INFORMATION

Date of preparation: July 2025

Version 1.04

Reason for change: Update

General:

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the work-place.

Since the supplier cannot anticipate or control the conditions under which this product may be used or handled, each user must, prior to using or handling this product, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is required to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers, and is also available from the company upon request.